

1 I claim:

2 1. A fishing lure comprising:

3 a body;

4 a hook secured to said body;

5 at least one opening extending into said body;

6 at least one sleeve securable in said at least one opening;

7 at least one elongated arm insertable and securable within said at least one

8 sleeve and extending from said body.

9 2. A fishing lure as recited in Claim 1 wherein said sleeve is crimped to secure said

10 at least one elongated arm within said at least one sleeve.

11 3. A fishing lure as recited in Claim 2 wherein said at least one elongated arm is

12 flexible.

13 4. A fishing lure as recited in Claim 3 wherein said at least one elongated arm

14 extends outwardly and backwardly from said body.

15 5. A fishing lure as recited in Claim 4 further comprising at least one spinning

16 element swivelly connected to a distal end of said at least one elongated arm.

17 6. A fishing lure as recited in Claim 5 further comprising:

18 a wire shank extending into and from said body;

19 a spinning element swivelly connected to a distal end of said wire shank.

20 7. A fishing lure as recited in Claim 6 wherein said body is lead and has a wider

21 head portion and a narrower tail portion.

1 8. A fishing lure as recited in Claim 7 further comprising a skirt attached to said tail  
2 portion.

3 9. A fishing lure as recited in Claims 1, 2, or 3, wherein said at least one elongated  
4 arm is wire.

5 10. A fishing lure comprising:

6 a body;

7 a hook securable to said body;

8 at least one opening extending into said body;

9 at least one sleeve within said at least one opening and extending from said  
10 body;

11 at least one wire arm securable within said at least one sleeve and extending  
12 outwardly and backwardly from said body wherein said at least one sleeve is crimped to  
13 secure said at least one wire arm.

14 11. A fishing lure as recited in Claim 10 wherein said at least one wire arm is  
15 flexible cable wire.

16 12. A fishing lure as recited in Claims 10 and 11 wherein said at least one opening  
17 being first and second openings positioned on opposite sides of said body, and said at  
18 least one sleeve being first and second sleeves securable within said first and second  
19 openings and extending from said body and said at least one wire arm being first and  
20 second wire arms.

21

22

- 1 13. A method for manufacturing a fishing lure comprising the steps of:  
2 attaching at least one hook to a lure body;  
3 forming at least one opening in said lure body;  
4 securing at least one sleeve within said at least one opening;  
5 inserting at least one arm into said at least one sleeve;  
6 crimping said at least one sleeve to secure said at least one arm within said  
7 sleeve.
- 8 14. The method for manufacturing a fishing lure as recited in Claim 13 wherein said  
9 arm is wire.
- 10 15. The method for manufacturing a fishing lure as recited in Claim 14 wherein said  
11 wire is flexible cable.
- 12 16. A method for manufacturing a fishing lure comprising the following steps:  
13 forming at least one mold cavity in the shape of a body of a fishing lure within a  
14 mold forming piece wherein said at least one mold cavity having at least one impression  
15 for receiving at least one connector sleeve;  
16 receiving said at least one connector sleeve into said at least one impression;  
17 introducing liquefied lure body material into said at least one mold cavity;  
18 cooling said lure body material within said at least one mold cavity until said  
19 lure body material hardens forming at least one lure body;  
20 removing said at least one lure body from said at least one mold cavity;  
21 inserting at least one arm into said at least one connector sleeve;  
22 crimping said at least one connector sleeve around said at least one arm to

1 secure said at least one arm within said at least one connector sleeve.

2 17. The method for manufacturing a fishing lure as recited in Claim 16 further  
3 comprising the step of placing at least one hook and at least one shank within each of  
4 said at least one mold cavity prior to introducing said liquefied lure body material  
5 wherein said at least one hook and said at least one shank extend outward from said at  
6 least one mold cavity.

7 18. The method for manufacturing a fishing lure as recited in Claim 17 wherein said  
8 at least one arm is wire.

9 19. The method for manufacturing a fishing lure as recited in Claim 18 wherein said  
10 at least one arm is flexible wire.

11 20. The method for manufacturing a fishing lure as recited in Claim 17 wherein at  
12 least one mold cavity is a plurality of mold cavities then said mold forming piece in said  
13 introducing step further comprises the steps of:

14 spinning said mold forming piece in a centrifugal device;  
15 pouring liquefied lure body material into an opening in said mold forming piece;  
16 channeling said liquefied lure body material into said plurality of mold cavities.